



RKSfluid®

A key Valve in Flow Control



Butterfly Valve




Ball Valve



Gate Valve



Globe Valve



Check Valve



Pipe Fittings



Resilient seat butterfly valve

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange



Resilient seat butterfly valve

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: DI+ Nylon

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange



Resilient seat butterfly valve

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange



Resilient seat butterfly valve

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange



Double flange resilient seat butterfly valve

PN10/PN16, ANSI 125LB/150LB, 5K/10K

Size:DN50-DN1000

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Flange



Short-neck butterfly valve for petroleum

ANSI 125LB/150LB

Top Flange Standard:ISO5211

Size:2"-12"

Body: DI CI

Disc :Stainless Steel

Seat : EPDM, NBR, Viton

Connection:Wafer, Lug



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: Ductile Iron

Disc: Ductile Iron+PTFE

Seat: PTFE

Connection: Wafer, Lug, Flange



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: Ductile Iron

Disc: Ductile Iron+PTFE

Seat: PTFE

Connection: Wafer, Lug, Flange



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: WCB, CF8, CF8M

Disc: CF8+PTFE, CF8M+PTFE

Seat: PTFE

Connection: Wafer, Lug



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: WCB, CF8, CF8M

Disc: CF8+PTFE, CF8M+PTFE

Seat: PTFE

Connection: Wafer, Lug



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: Ductile Iron

Disc: CF8, CF8M

Seat: PTFE

Connection: Wafer, Lug, Flange



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: WCB

Disc: CF8 +PTFE, CF8 +PFA

Seat: PTFE

Connection: Wafer, Lug, Flange

APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport



Our Factory



O fluido RKS foi fundado em 1997. Somos um laboratório de produção tanto para fundição quanto para processamento mecânico, centro de pesquisa e desenvolvimento e centro de controle de qualidade. As instalações de produção incluem centros de trabalho numéricos, células de processamento profissional, equipamentos de soldagem de amplo espectro, montagem automática e linhas de revestimento. Criamos uma equipe para design, pesquisa e

desenvolvimento. Nosso novo centro de testes como centro de testes de plataforma pública na província de Liaoning torna-se o GB padrão da unidade de referência da válvula chinesa, para participar no desenvolvimento dos padrões da indústria válvula relacionados. A fim de acelerar a expansão dos negócios no exterior e a integração dos recursos e apoiar o sucesso das vendas de fluidos de RKs nos Estados Unidos, na Alemanha e na Rússia. Nós temos um agente americano. Nossos padrões de design de produto incluem: Padrões GB, ISO, Alemão e Americano, aprovados pela TUV para CE e ADWO-2000, ISO9001, TS, API. Nossos produtos: válvulas manuais, pneumáticas e e esferas, válvulas de borboleta e válvulas eletricamente operadas. Verifique as válvulas, válvulas de controle automáticas. Castings e acessórios: corpos de válvulas, capuzes, discos, caules, caixa de engrenagens, juntas universais, adaptadores de flange, tampas de sela. Depois de anos de desenvolvimento, continuamos a melhorar e buscar a inovação, aderindo a "tecnologia comprovada, recursos superiores e valor lendário" como nossa filosofia do valor do produto. A satisfação do cliente é o nosso objetivo de negócios!

Exhibition Photos



Our Certificates

