



RKSfluid®

A key Valve in Flow Control



Butterfly Valve



Ball Valve



Gate Valve



Globe Valve



Check Valve



Pipe Fittings



Resilient seat butterfly valve



Resilient seat butterfly valve



Resilient seat butterfly valve

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: DI+ Nylon

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange



Resilient seat butterfly valve



Double flange resilient seat butterfly valve



Short-neck butterfly valve for petroleum

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange

PN10/PN16, ANSI 125LB/150LB, 5K/10K

Size:DN50-DN1000

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Flange

ANSI 125LB/150LB

Top Flange Standard:ISO5211

Size:2"-12"

Body: DI CI

Disc :Stainless Steel

Seat : EPDM, NBR, Viton

Connection:Wafer, Lug



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: Ductile Iron

Disc: Ductile Iron+PTFE

Seat: PTFE

Connection: Wafer, Lug, Flange



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: Ductile Iron

Disc: Ductile Iron+PTFE

Seat: PTFE

Connection: Wafer, Lug, Flange



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: WCB, CF8, CF8M

Disc: CF8+PTFE, CF8M+PTFE

Seat: PTFE

Connection: Wafer, Lug



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: WCB, CF8, CF8M

Disc: CF8+PTFE, CF8M+PTFE

Seat: PTFE

Connection: Wafer, Lug



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: Ductile Iron

Disc: CF8, CF8M

Seat: PTFE

Connection: Wafer, Lug, Flange



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: WCB

Disc: CF8 +PTFE, CF8 +PFA

Seat: PTFE

Connection: Wafer, Lug, Flange



APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport



Our Factory



Company Advantages

01

21 years of professional experience

03

Independent research and development team
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06



RKSfluid 于 1997 年在中国山东省潍坊市成立，是一家专业从事工业气体净化、干燥、过滤、分离、回收等工程的设计、制造、安装、调试、运营、维护为一体的综合性企业。公司拥有先进的生产设备和专业的技术人才，为客户提供高品质的产品和服务。

公司主要产品包括：工业气体净化系统、工业气体干燥系统、工业气体过滤系统、工业气体分离系统、工业气体回收系统等。广泛应用于化工、医药、食品、电子、冶金、石油、天然气等行业。

公司通过了 GB、ISO、TUV 等国际认证，产品符合 CE、ADWO-2000、ISO9001、TS、API 等标准。公司拥有完善的质量管理体系和售后服务体系，为客户提供全方位的支持。

公司秉承“诚信、专业、创新、共赢”的经营理念，致力于为客户提供高品质的产品和服务。公司拥有完善的质量管理体系和售后服务体系，为客户提供全方位的支持。

公司主要产品包括：工业气体净化系统、工业气体干燥系统、工业气体过滤系统、工业气体分离系统、工业气体回收系统等。广泛应用于化工、医药、食品、电子、冶金、石油、天然气等行业。

公司通过了 GB、ISO、TUV 等国际认证，产品符合 CE、ADWO-2000、ISO9001、TS、API 等标准。公司拥有完善的质量管理体系和售后服务体系，为客户提供全方位的支持。

公司秉承“诚信、专业、创新、共赢”的经营理念，致力于为客户提供高品质的产品和服务。公司拥有完善的质量管理体系和售后服务体系，为客户提供全方位的支持。

... RKS
...
... GB, ISO, ... TUV ... CE
... ADWO-2000
ISO9001, TS, API ... & ...
...
...
...
... Saddle: ...
... " ...
...!
...
...

work ...

III ...

IV ...

Prodotto ... GB, ... TUV CE, ISO 9001, ADWO-2000, TS, PED, WRC WRAS, KTW, API 6D, API609

VI ... / ... / ...

Q: 100%의 수분 함유를 허용하는 윤활유가 있습니까?

A: 네, 있습니다. RKSfluid 100% 수분 함유를 허용하는 윤활유가 있습니다.

Q: RKSfluid 100% 수분 함유를 허용하는 윤활유가 있습니까?

A: RKSfluid 100% 수분 함유를 허용하는 윤활유가 있습니다.

Q: 수분 함유를 허용하는 윤활유가 있습니까?

A: 수분 함유를 허용하는 윤활유가 2 ~ 5 미크론의 입자 크기를 가진 윤활유가 있습니다.

Q: 수분 함유를 허용하는 윤활유가 있습니까?

A: 1 미크론 이하의 입자 크기를 가진 윤활유가 있습니다.

Q: 수분 함유를 허용하는 윤활유가 있습니까?

A: 100% 수분 함유를 허용하는 윤활유가 2 미크론 이하의 입자 크기를 가진 윤활유가 있습니다.

인증: TUV, API, WRAS, CE, ISO

인증: DIN, ASME, BS EN, JIS, API, AWWA

Q: 수분 함유를 허용하는 윤활유가 있습니까?

A: RKSfluid 100% 수분 함유를 허용하는 윤활유가 20 미크론 이하의 입자 크기를 가진 윤활유가 70 미크론 이하의 입자 크기를 가진 윤활유가 있습니다.