



RKSfluid®

A key Valve in Flow Control



Butterfly Valve



Ball Valve



Gate Valve



Globe Valve




Check Valve



Pipe Fittings

DESIGN FEATURES

- RANGE**
- For CI, DI, STL and AC pipes
 - **DN50-DN1000**
 - The body & gasket fit **9 kinds of pipe** with nominal diameters
 - The saddles – Can be used for **all pipe types**



- RELIABLE**
- **EPDM gasket** to EN681-1, mechanically inserted on Series 1425

- ANTI-CORROSION**
- Epoxy or cathodolysis coating
 - Thickness: Epoxy powder coating of **200-250µm**
 - Temperature : Spraying temperature over **200 °C**. Doesn't fade, even wipe with **diethyl ether**.

MATERIAL

- Epoxy powder:  , Earth Best!
- Nuts: **DACROMET®** or **GEOMET®** , Earth Best!
- Cast iron: **EN-GJS-400-15**, nodularity over **95%**!



APPLICATION SCENARIO



Industrial water application



Hydroelectric generation



Sewage treatment



Water treatment



Water supply and drainage



Water transport



Pipe network in house



Irrigation



Our Factory



Company Advantages

01

21 years of professional experience

03

Independent research and development team
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06



i

centers

reference

IV

Standard GB, TUV CE, ISO 9001,

ADWO-2000, TS, PED, WRC WRAS, KTW, API 6D, API609

VI 公司： 公司， 公司， 公司， 公司， 公司， 公司， 公司 / 公司 / 公司， 公司

Exhibition Photos



Our Certificates



公司

公司： 公司
公司： 公司

公司： 公司
A: 公司， 公司， Hydraulic， 公司 RKSfluid 公司
公司 公司

Q: 100% 100% 100% 100% 100% 100% 100% 100% 100% 100%

A: RKSfluid 100% 100% 100% 100% 100% 100% 100% 100% 100% 100%

Q: 100% 100% 100%

A: 100% 100% 100% 100% 100% 100% 100% 100% 100% 100%

Q: 100% 100%

A: 1 100% 100% 100% 100% 100% 100% 100% 100%

100%: 100% 100% 100% 100% 100% 100% 100% 100%

A: 100% 100% 100% 100% 100% 100% 100% 100% 100% 100%

100% 100% TUV, API, WRAS, CE, ISO 100%

100% 100% DIN, ASME, BS EN, JIS, API, AWWA

100%: 100% 100% 100% 100% 100% 100% 100% 100%

A: RKSfluid 100% 100% 100% 100% 100% 100% 100% 100%