DESIGN FEATURES

PE — Polyethylene
PVC — Poly Vinyl Chloride

RANGE

- For PE and PVC pipes
- Dimension from 32-400mm
- Threaded boss or flange connection
- Female threaded boss outlets from1/2" to 2" or flange outlets from DN40 to DN150
- Steel bolts and washers, M8, M10 or M12, A2 or AISI304

RELIABLE

- Saddle and strap fully screwed tight together

ANTI-CORROSION

- Thickness: Epoxy powder coating of 150-200μm
- Temperature : Spraying temperature over 200 ℃ Doesn't fade, even wipe with diethyl ether

MATERIAL

- Epoxy powder: AkzoNobel , Earth Best!
- Nuts: DACROMET® or GEOMET®, Earth Best!
- Cast iron: EN-GJS-400-15 or EN-GJS-500-7, nodularity over 95%!

APPLICATION SCENARIO

Industrial water application | Hydroelectric generation | Sewagetreatment | Water treatment | Water supply and drainage | Water transport | Pipe network in house | Irrigation

Our Factory

Company Advantages

01 21 years of professional experience

02 4 factories

03 Independent research and development team
28 top senior professional researchers

04 2 professional testing centers

05 100% high level ex-factory inspection

06 High quality imported materials

07 2 years quality assurance, repair and replacement

area □□□□□□□□□□□□□□: □□□
□

centers □□□
□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

reference □□□
□□□□□□□□□□□□□

IV□□

Standard □□□□□□□□□□□□□□□□: GB, □□□□□□□□□□□□□□□, □□□□□□□□□□□□□□□□□□, TUV CE, ISO 9001, ADWO-2000, TS, PED, WRC WRAS, KTW, API 6D, API609

VI □□□□□□□□□□□□: □□□□□□□□□□□□, □□□□□□□□, □□□□□□□□□□□, □□□□□□□□□□□□□, □□□□□□□□, □□□□□□□ □□□, □□□□□□ / □□□□□□□□ / □□□□□□□□□□□□□□□□, □□□□□□□□□□□□□

Exhibition Photos

Our Certificates

[illegible]

[illegible]: [illegible]
[illegible]: [illegible]

[illegible]: [illegible]

A: [illegible], [illegible], Hrdraulic, [illegible] [illegible] RKSfluid [illegible]
[illegible] [illegible]

Q: [illegible]

A: RKSfluid [illegible]

Q: [illegible]

A: [illegible] 2 ~ 5 [illegible] [illegible]

Q: [illegible]

A: 1 [illegible]

[illegible]: [illegible]

A: 100% [illegible] 2 [illegible] [illegible]
[illegible]

[illegible] TUV, API, WRAS, CE, ISO [illegible]

[illegible] DIN, ASME, BS EN, JIS, API, AWWA

[illegible]: [illegible]

A: RKSfluid [illegible] 20 [illegible] 70 [illegible]
[illegible]