

DESIGN FEATURES

This series of butterfly valves are used for industrial pipelines, as bi-directional open and close and regulation devices, the adjustment range is from 40°C-90°C full open. Suitable temperature $\geq 80^{\circ}\text{C}$

Features

- Size range DN100-1200mm
- Standard-ISO/BS/DIN/AWWA/API
- Tests Standard-BS EN 12266-1
- Body-Ductile Iron/Cast Iron/Stainless Steel /WCB
- Body Ring-SS420/SS304/SS316
- Disc Ring-EPDM
- Shaft-SS420/SS431/SS316
- Fusion bonded epoxy coating-Min 300 Microns



APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport



COMPANY FACTORY



COMPANY INFORMATION



i 本公司拥有完善的质量管理体系，通过了 ISO 9001 质量管理体系认证，确保了产品质量的稳定性和可靠性。

ii 本公司拥有先进的 CNC 加工设备，能够满足各种复杂零件的加工需求，加工精度高，交货周期短。

unit 本公司拥有专业的技术团队，能够为客户提供专业的技术支持和售后服务，确保客户满意。

iv 本公司拥有完善的安全管理体系，通过了 ISO 45001 职业健康安全管理体系认证，确保了员工的安全和健康。

v 本公司拥有完善的环境管理体系，通过了 ISO 14001 环境管理体系认证，符合 GB, ADWO-2000, TS, PED, WRC WRAS, KTW, API 6D, API609 等标准。

VI 本公司拥有完善的信息管理体系，通过了 ISO 27001 信息安全管理体系认证，确保了客户信息的安全。



COMPANY QUALIFICATION



