

DESIGN FEATURES



● TECHNICAL REQUIREMENT

- 1.Design standard:BS 5163.
- 2.Face to face:BS 5163.
- 3.Flanges standard:BS EN1092-2:1997 PN16.
- 4.Test standard:BS EN12266-1 Rate B.

● FEATURES

- Double flange metal seated gate valve
- Size Range:DN50-DN2000
- Standard-ISO/BS/DIN/AWWA/API
- Tests Standard-BS EN 12266-1
- Body Ring-Bronze/SS420/SS304/SS316
- Body-Ductile Iron /Cast Iron/Stainless Steel /WCB
- Fusion bonded epoxy coating-min 300 microns



RELATED PRODUCTS



SMALL DIAMETER GATE VALVE
DN50-DN300,PN10/16/25



METAL SEATED GATE VALVE
DN350-DN600,PN10/16/25



LARGE DIAMETER METAL SEATED GATE VALVE
DN700-DN2000,PN10/16/25



01

21 years of professional experience

03

Independent research and development team
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06

COMPANY QUALIFICATION



COMPANY EXHIBITION



Q: How long does it take to receive the product?

A: It depends on the product and the quantity.

Q: RKSfluid is a new company, how do you guarantee the quality?

D: We have a long history in the industry.

Q: How many years have you been in the market? 2 ~ 5 years?

D: 1 year.

Q: 1 year is very short, how do you guarantee the quality?

A: We have a strong R&D team.

Q: How long does it take to receive the product? 100%? 2 years?

We have a strong R&D team and we are certified by Tuv, Api, Wras, CE, ISO, DIN, ASME, BS EN, JIS, API, Awwa.

Q: How long does it take to receive the product? 20 years?

A: RKSfluid has been in the market for 20 years. We have a strong R&D team and we are certified by Tuv, Api, Wras, CE, ISO, DIN, ASME, BS EN, JIS, API, Awwa.