

https://www.alibaba.com/product-detail/DIN-STANDARD-CAST-IRON-METAL-SEAL_1600089458994.html?spm=a2747.manage.0.0.516371d2z5mxtO



Product Description



Super Anti-corrosion
Epoxy powder coating **200-250 μ m**,
baking varnish over **200°C**,
use  material.



Free wedge nut, **reduces the stem bending forces** and at the same time enables it to be easily replaced.



The more compact new cap, reduces the water retention areas in order to **reduce the risk of bacterial growth**.



One piece stainless steel stem in for **better resistance to axial load and to with stand higher operating torques**.



Three locking tab for bayonet system prevents self-dismantling.



Dust guard integrating three O-ring shape, **prohibiting the introduction of foreign** bodies at the stem.



Male guiding system with composite sliding skate reduces the wear of the wedge against the body, allowing a smooth functionality and a longer life time of the valve.



Triple seal at the operating stem to ensure tightness with the test of time (2500 cycles).



New male composite sliding skate technology ensuring a low operating torque even under high differential pressure and preventing damage or corrosion generated by the friction.

Engineering Projects



Product Category



PTFE lined butterfly valve



Resilient seat butterfly valve



Double offset butterfly valve



Triple offset butterfly valve



Ball valve



Pipe fittings



ADWO-2000, TS, PED, WRC WRAS, KTW, API 6D, API609

VI 认证：ISO 9001, ISO 14001, ISO 45001, API 6D, API 609, PED, WRC WRAS, KTW, ADWO-2000, TS, PED, WRC WRAS, KTW, API 6D, API 609

Our Factory



Exhibition Photos



Our Certificates



□ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □

:

[illegible]

QUESTION: _____?

