Design Features

APPLICATION

- Super large diameters up to DN4000 and beyond! Greater adjustability, greater DN/PN in many challenging projects worldwide
- Fast, efficient installation & dismantlement

CLASSIC & STURDY DESIGN

- AWWA-C219 absolutely leakproof
- Independent gasket
- Perfectly balanced economical & technical superior

HIGHLY CUSTOMIZABLE

- According to customer requirement

DURABLE

- ANTI-CORROSION
- Thickness: Epoxy powder coating of 150-200 μm
- Temperature : Spraying temperature over 200℃. Doesn't fade, even wipe with diethyl ether

MATERIAL

- Epoxy powder: AkzoNobel, Earth Best!
- WRAS, KTW-W270, ACS approved materials
- Cast iron: nodularity over 95%!
- Bolts, nuts & washers: Hot Dip Galvanized or Stainless Steel AISI316-A4

Application Scenario

Our Factory

Company Advantages

01 21 years of professional experience

02 4 factories

03 Independent research and development team
28 top senior professional researchers

04 2 professional testing centers

05 100% high level ex-factory inspection

06 High quality imported materials

07 2 years quality assurance, repair and replacement

area □□□□□□□□□□□□□□: □□
□

II□□
□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

reference □□□
□□□□□□□□□□□□□□

IV□□

Standard □□□□□□□□□□□□□□□□□: GB, □□□□□□□□□□□□□□□, □□□□□□□□□□□□□□□□□□, TUV CE, ISO 9001, ADWO-2000, TS, PED, WRC WRAS, KTW, API 6D, API609

VI □□□□□□□□□□□□: □□□□□□□□□□□□□, □□□□□□□□, □□□□□□□□□□□, □□□□□□□□□□□□□, □□□□□□□□, □□□□□□□ □□□□, □□□□□□ / □□□□□□□□ / □□□□□□□□□□□□□□□□□, □□□□□□□□□□□□□□

Exhibition Photos

Our Certificates

[illegible]

[illegible]: [illegible]
[illegible]: [illegible]

[illegible]: [illegible]

A: [illegible], [illegible], Hrdraulic, [illegible] [illegible] RKSfluid [illegible] [illegible] [illegible]

Q: [illegible]

A: RKSfluid [illegible]

Q: [illegible]

A: [illegible] 2 ~ 5 [illegible] [illegible]

Q: [illegible]

A: 1 [illegible]

[illegible]: [illegible]

A: 100% [illegible] 2 [illegible] [illegible] [illegible]

[illegible] TUV, API, WRAS, CE, ISO [illegible]

[illegible] DIN, ASME, BS EN, JIS, API, AWWA

[illegible]: [illegible]

A: RKSfluid [illegible] 20 [illegible] 70 [illegible] [illegible]