

RKSfluid®



口径	DN32 - DN2400 (NPS1 1/4-NPS96)
公称压力	PN6 - PN10 - PN16 (ANSI 150)
使用温度	-40°C-120°C
密封材料	丁腈橡胶, 三元乙丙橡胶
适用介质	NBR, EPDM, 海水, 工业用水, 蒸汽
连接形式	Wafer, Lug, U-Section, 法兰

APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport



COMPANY INFORMATION



I 公司宗旨： 秉承“以人为本、科技领先、服务至上”的经营理念，为客户提供高品质的产品和服务。

II 公司使命： 致力于成为全球领先的工业解决方案提供商，通过技术创新和卓越服务，为客户创造价值。

III 公司愿景： 成为行业标杆，引领行业发展，实现可持续发展。

IV 公司优势： 拥有先进的生产设备、专业的技术团队和完善的售后服务体系。

V 公司资质： GB, ISO 9001, TUV CE, ADWO-2000, TS, PED, WRC WRAS, KTW, API 6D, API609

VI 公司地址： 中国广东省广州市天河区珠江新城， 邮编：510623， 电话：020-88888888， 邮箱：info@company.com



01

21 years of professional experience

03

Independent research and development team
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06

COMPANY QUALIFICATION



COMPANY EXHIBITION



