



RKSfluid®

A key Valve in Flow Control



Butterfly Valve



Ball Valve



Gate Valve



Globe Valve



Check Valve



Pipe Fittings



Resilient seat butterfly valve



Resilient seat butterfly valve



Resilient seat butterfly valve

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: DI+ Nylon

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange



Resilient seat butterfly valve



Double flange resilient seat butterfly valve



Short-neck butterfly valve for petroleum

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange

PN10/PN16, ANSI 125LB/150LB, 5K/10K

Size:DN50-DN1000

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Flange

ANSI 125LB/150LB

Top Flange Standard:ISO5211

Size:2"-12"

Body: DI CI

Disc :Stainless Steel

Seat : EPDM, NBR, Viton

Connection:Wafer, Lug



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: Ductile Iron

Disc: Ductile Iron+PTFE

Seat: PTFE

Connection: Wafer, Lug, Flange



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: Ductile Iron

Disc: Ductile Iron+PTFE

Seat: PTFE

Connection: Wafer, Lug, Flange



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: WCB, CF8, CF8M

Disc: CF8+PTFE, CF8M+PTFE

Seat: PTFE

Connection: Wafer, Lug



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: WCB, CF8, CF8M

Disc: CF8+PTFE, CF8M+PTFE

Seat: PTFE

Connection: Wafer, Lug



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: Ductile Iron

Disc: CF8, CF8M

Seat: PTFE

Connection: Wafer, Lug, Flange



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: WCB

Disc: CF8 +PTFE, CF8 +PFA

Seat: PTFE

Connection: Wafer, Lug, Flange



APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport



Our Factory



Company Advantages

01

21 years of professional experience

03

Independent research and development team
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06



RKSfluid 自 1997 年成立以来，始终秉承“质量第一、客户至上”的经营理念，为客户提供高品质的产品和服务。我们拥有先进的生产设备和专业的技术团队，确保每一件产品都符合国际标准和客户要求。

我们的产品和服务广泛应用于各个行业，包括食品加工、制药、化工、电子等。我们拥有完善的质量管理体系，通过了 GB、ISO、TUV 等多项国际认证，确保产品的可靠性和稳定性。

我们拥有完善的质量管理体系，通过了 GB、ISO、TUV 等多项国际认证，确保产品的可靠性和稳定性。我们的产品和服务广泛应用于各个行业，包括食品加工、制药、化工、电子等。

我们的产品和服务广泛应用于各个行业，包括食品加工、制药、化工、电子等。我们拥有完善的质量管理体系，通过了 GB、ISO、TUV 等多项国际认证，确保产品的可靠性和稳定性。

我们的产品和服务广泛应用于各个行业，包括食品加工、制药、化工、电子等。我们拥有完善的质量管理体系，通过了 GB、ISO、TUV 等多项国际认证，确保产品的可靠性和稳定性。

我们的产品和服务广泛应用于各个行业，包括食品加工、制药、化工、电子等。我们拥有完善的质量管理体系，通过了 GB、ISO、TUV 等多项国际认证，确保产品的可靠性和稳定性。我们拥有完善的质量管理体系，通过了 GB、ISO、TUV 等多项国际认证，确保产品的可靠性和稳定性。

我们的产品和服务广泛应用于各个行业，包括食品加工、制药、化工、电子等。我们拥有完善的质量管理体系，通过了 GB、ISO、TUV 等多项国际认证，确保产品的可靠性和稳定性。

我们的产品和服务广泛应用于各个行业，包括食品加工、制药、化工、电子等。我们拥有完善的质量管理体系，通过了 GB、ISO、TUV 等多项国际认证，确保产品的可靠性和稳定性。

我们的产品和服务广泛应用于各个行业，包括食品加工、制药、化工、电子等。我们拥有完善的质量管理体系，通过了 GB、ISO、TUV 等多项国际认证，确保产品的可靠性和稳定性。

我们的产品和服务广泛应用于各个行业，包括食品加工、制药、化工、电子等。我们拥有完善的质量管理体系，通过了 GB、ISO、TUV 等多项国际认证，确保产品的可靠性和稳定性。

... RKS
...
...

... GB, ISO, ... TUV ... CE
... ADWO-2000

ISO9001, TS, API ... & ...

...
...
...

Saddle: ...
"..."
...

...!
...
...

work ...

III ...

IV ...

Prodotto ... GB, ... TUV CE, ISO 9001,
ADWO-2000, TS, PED, WRC WRAS, KTW, API 6D, API609

VI ... / ... / ...

Q: 100%의 수분 함유를 허용하는 윤활유가 있습니까?

A: 네, 있습니다. RKSfluid 100% 수분 함유를 허용하는 윤활유가 있습니다.

Q: RKSfluid 100% 수분 함유를 허용하는 윤활유가 있습니까?

A: 네, RKSfluid 100% 수분 함유를 허용하는 윤활유가 있습니다.

Q: RKSfluid 100% 수분 함유를 허용하는 윤활유가 있습니까?

A: RKSfluid 100% 수분 함유를 허용하는 윤활유는 2 ~ 5 미터의 수심에서 작동하는 펌프에 적합합니다.

Q: RKSfluid 100% 수분 함유를 허용하는 윤활유가 있습니까?

A: 네, RKSfluid 100% 수분 함유를 허용하는 윤활유가 있습니다.

Q: RKSfluid 100% 수분 함유를 허용하는 윤활유가 있습니까?

A: 100% 수분 함유를 허용하는 윤활유는 2 미터의 수심에서 작동하는 펌프에 적합합니다.

RKSfluid 100% 수분 함유를 허용하는 윤활유는 TUV, API, WRAS, CE, ISO

인증된 윤활유입니다. DIN, ASME, BS EN, JIS, API, AWWA

Q: RKSfluid 100% 수분 함유를 허용하는 윤활유가 있습니까?

A: RKSfluid 100% 수분 함유를 허용하는 윤활유는 20 미터의 수심에서 작동하는 펌프에 적합하며 70 미터의 수심에서 작동하는 펌프에 적합합니다.