



## DESIGN FEATURES

### TECHNICAL REQUIREMENT

- 1.Design standard:BS 5163.
- 2.Face to face:BS 5163.
- 3.Flanges standard:BS EN1092-2:1997 PN16.
- 4.Test standard:BS EN12266-1 Rate B.

### FEATURES

- Double flange metal seated gate valve
- Size Range:DN50-DN2000
- Standard-ISO/BS/DIN/AWWA/API
- Tests Standard-BS EN 12266-1
- Body Ring-Bronze/SS420/SS304/SS316
- Body-Ductile Iron /Cast Iron/Stainless Steel /WCB
- Fusion bonded epoxy coating-min 300 microns



## RELATED PRODUCTS

---



SMALL DIAMETER GATE VALVE  
DN50-DN300,PN10/16/25



METAL SEATED GATE VALVE  
DN350-DN600,PN10/16/25



LARGE DIAMETER  
METAL SEATED GATE VALVE  
DN700-DN2000,PN10/16/25

## APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport



## COMPANY FACTORY



## COMPANY INFORMATION



i 本公司拥有先进的生产设备，采用国际先进的生产工艺，确保产品质量稳定可靠。

ii 本公司拥有完善的质量管理体系，通过 ISO 9001 认证，严格执行国家标准，确保产品质量符合客户要求。

unit 本公司拥有专业的技术团队，具备丰富的生产经验，能够为客户提供专业的技术支持和售后服务。

iv 本公司拥有完善的生产流程，从原材料采购到成品出厂，每个环节都严格把控，确保产品质量。

v 本公司拥有完善的质量管理体系，通过 GB, ISO 9001, TUV CE, ADWO-2000, TS, PED, WRC WRAS, KTW, API 6D, API609 等认证，确保产品质量符合国际标准。

VI 本公司拥有完善的质量管理体系，通过 GB, ISO 9001, TUV CE, ADWO-2000, TS, PED, WRC WRAS, KTW, API 6D, API609 等认证，确保产品质量符合国际标准。

01

21 years of professional  
experience

03

Independent research and  
development team  
28 top senior professional  
researchers

05

100% high level ex-factory  
inspection

07

2 years quality assurance,  
repair and replacement

4 factories

02

2 professional testing  
centers

04

High quality imported  
materials

06

# COMPANY QUALIFICATION



[illegible]

**□ □ : □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ ?**

:

[illegible]

**000:** 00000000, 00000, hrdraulic, 0000000000000 RKSfluid Actuators 000000000000000000  
0000000 00000000000000000000000000

**□ □ □ : □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ ?**

```

RKSfluid

```

□□□□ : □□□□□□□□□□□□□□□□

□□□□ : □□□□□□□□□□□□□□□□□□□□ 2 ~ 5 □□□□□□□□ □□□□□□□□□□□□□□□□□□□□□□□□□□

```
00000000: mov
```

A: 1pc

**□ □ □ □ : □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ ?**

0000: 0000000000000000 100% 0000000000000000 2 00 000000000000000000000000  
0000000000000000

□□□□□□□□ TUV, API, WRAS, CE, □□□□□□□□ ISO

DIN, ASME, BS EN, JIS, API, AWWA

**QUESTION**

[illegible]