

## DESIGN FEATURES



### ● TECHNICAL REQUIREMENT

- 1.Design standard:BS 5163.
- 2.Face to face:BS 5163.
- 3.Flanges standard:BS EN1092-2:1997 PN16.
- 4.Test standard:BS EN12266-1 Rate B.

### ● FEATURES

- Double flange metal seated gate valve
- Size Range:DN50-DN2000
- Standard-ISO/BS/DIN/AWWA/API
- Tests Standard-BS EN 12266-1
- Body Ring-Bronze/SS420/SS304/SS316
- Body-Ductile Iron /Cast Iron/Stainless Steel /WCB
- Fusion bonded epoxy coating-min 300 microns



**RELATED PRODUCTS**



**SMALL DIAMETER GATE VALVE**  
DN50-DN300,PN10/16/25



**METAL SEATED GATE VALVE**  
DN350-DN600,PN10/16/25



**LARGE DIAMETER METAL SEATED GATE VALVE**  
DN700-DN2000,PN10/16/25

COMPANY FACTORY







# COMPANY FACTORY



01

21 years of professional experience

03

Independent research and development team  
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06

# COMPANY QUALIFICATION







Q: 貴社はどのような製品を扱っていますか？

A: RKSfluid は、流体制御用の各種バルブ、ポンプ、配管システムを提供しています。

Q: 貴社の強みは何ですか？

A: 20年以上の経験と、2~5名の専門スタッフが、お客様のニーズに合わせた最適なソリューションを提供しています。

Q: **moq**

A: 1pc からのご注文も承ります。

Q: 貴社の製品はどのような規格に準拠していますか？

A: 100%の品質保証と、2年間の保証期間を提供しています。また、ISO 9001:2015に準拠しています。

また、TUV, API, WRAS, CE, ISO 9001:2015に準拠しています。

また、DIN, ASME, BS EN, JIS, API, AWWAに準拠しています。

Q: 貴社の製品はどのような用途に使用されていますか？

A: RKSfluid は、20年以上の経験と、R&Dに70%以上のリソースを投入し、お客様のニーズに合わせた最適なソリューションを提供しています。