



## DESIGN FEATURES

### DURABLE

- No-pin connection, 1 pc blow-out proof stem
- DI/CI Nodularity over 95%

### ANTI-CORROSION

- Material: Epoxy powder:  Earth Best!
- Coating Thickness: 200-250µm
- Spraying temp: over 200°C. Doesn't fade, even wipe with diethyl ether

### QUALITY STANDARD

- 100% quality test, follow DIN, ASTM, JIS, GB/T, ISO, BS EN, API
- ONLY ONE Manufacturer get CE certification up to DN1800
- 2 years warranty. 15000 times On-off test, 30000 times Destructive experiment



# APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport



# COMPANY FACTORY



# COMPANY INFORMATION



i) 本公司提供之產品均符合 ISO 9001 國際標準，並獲得 ISO 9001 國際認證。

ii) 本公司提供之產品均採用 CNC 加工，精確度極高，且具備優良之機械性能，並符合 ISO 9001 國際標準。

unit 本公司提供之產品均符合 ISO 9001 國際標準，並獲得 ISO 9001 國際認證。

iv) 本公司提供之產品均符合 ISO 9001 國際標準，並獲得 ISO 9001 國際認證。

v) 本公司提供之產品均符合 GB, ISO 9001, TUV CE, ISO 9001, ADWO-2000, TS, PED, WRC WRAS, KTW, API 6D, API609

VI) 本公司提供之產品均符合 ISO 9001 國際標準，並獲得 ISO 9001 國際認證，並符合 ISO 9001 國際標準，並符合 ISO 9001 國際標準。



## COMPANY QUALIFICATION





