

DESIGN FEATURES



● TECHNICAL REQUIREMENT

- 1.Design standard:BS 5163.
- 2.Face to face:BS 5163.
- 3.Flanges standard:BS EN1092-2:1997 PN16.
- 4.Test standard:BS EN12266-1 Rate B.

● FEATURES

- Double flange metal seated gate valve
- Size Range:DN50-DN2000
- Standard-ISO/BS/DIN/AWWA/API
- Tests Standard-BS EN 12266-1
- Body Ring-Bronze/SS420/SS304/SS316
- Body-Ductile Iron /Cast Iron/Stainless Steel /WCB
- Fusion bonded epoxy coating-min 300 microns



RELATED PRODUCTS



SMALL DIAMETER GATE VALVE
DN50-DN300,PN10/16/25



METAL SEATED GATE VALVE
DN350-DN600,PN10/16/25



LARGE DIAMETER METAL SEATED GATE VALVE
DN700-DN2000,PN10/16/25

APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport



COMPANY INFORMATION



I 本公司提供： 各种规格、材质、口径的工业阀门、水泵、管件、法兰、密封件、过滤器、换热器、冷却塔、水箱、水池、污水处理设备等。

II 本公司提供： CNC 加工服务，承接各种精密机械加工、模具制造、非标零件加工、钣金加工、表面处理等。

III 鋼製球閥の製造工程は、材料の選定、鍛造、熱処理、研磨、検査の順に進みます。また、球の研磨精度は、製品の性能に大きく影響します。

IV 鋼製球閥の構造は、球、球座、球座リング、球座リングリング、球座リングリングリングの順に進みます。

V 鋼製球閥の規格: GB, 鋼製球閥の規格, 鋼製球閥の規格, Tuv CE, ISO 9001, ADWO-200, TS, PED, WRC WRAS, KTW, API 6D, API609

鋼製球閥の材質: 鋼製球閥の材質, 鋼製球閥の材質, 鋼製球閥の材質, 鋼製球閥の材質, 鋼製球閥の材質, 鋼製球閥の材質, 鋼製球閥の材質 / 鋼製球閥の材質 / 鋼製球閥の材質, 鋼製球閥の材質



01

21 years of professional experience

03

Independent research and development team
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06

COMPANY QUALIFICATION



COMPANY EXHIBITION



Partners



Delivery



Payment



□□□□□□□□□□□□□□

□□: □□□□□□□□□□□□□□□□ □□□□□□□□□□□□□□□□□□□□
 □□: □□□□□□□□ □□□□□□ □□□□□□ □□□□□□□□□□□□□□

□□: □□□□□□□□□□□□□□□□□□□□ □□□□□□□□□□□?
 □□: □□□□□□□, □□□□□, Hrdraulic, □□□□□□□□□□□□ RKSfluid □□□□□□□□□□□□□□□□□□□□

