



RKSfluid®

A key Valve in Flow Control



Butterfly Valve



Ball Valve



Gate Valve



Globe Valve



Check Valve



Pipe Fittings

Product Description



Super Anti-corrosion
Epoxy powder coating **200-250µm**,
baking varnish over **200°C**,
use  material.



Free wedge nut, **reduces the stem bending forces** and at the same time enables it to be easily replaced.



The more compact new cap, reduces the water retention areas in order to **reduce the risk of bacterial growth**.



One piece stainless steel stem in for **better resistance to axial load and to with stand higher operating torques**.



Three locking tab for bayonet system prevents self-dismantling.



Dust guard integrating three O-ring shape, **prohibiting the introduction of foreign bodies** at the stem.



Male guiding system with composite sliding skate reduces the wear of the wedge against the body, allowing a smooth functionality and a longer life time of the valve.



Triple seal at the operating stem to ensure tightness with the test of time (2500 cycles).



New male composite sliding skate technology ensuring a low operating torque even under high differential pressure and preventing damage or corrosion generated by the friction.

Engineering Projects



Product Category





Standard 认证: GB, ISO 9001, TUV CE, ISO 9001, ADWO-2000, TS, PED, WRC WRAS, KTW, API 6D, API609

VI 认证: CE, ISO 9001, ISO 14001, ISO 45001, API 6D, API 609, WRC WRAS, KTW, PED, ADWO-2000, TS, GB

Our Factory



Exhibition Photos



Our Certificates



□□□□□□□□□□□□□□

□□: □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

□□: □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

□□: □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

A: RKSfluid, Hydraulic, RKSfluid

Q:

A: RKSfluid

Q:

A: 2 ~ 5

Q:

A: 1

Q:

A: 100% 2

TUV, API, WRAS, CE, ISO
DIN, ASME, BS EN, JIS, API, AWWA

Q:

A: RKSfluid 20 R&D 70