

DESIGN FEATURES



● TECHNICAL REQUIREMENT

- 1.Design standard:BS 5163.
- 2.Face to face:BS 5163.
- 3.Flanges standard:BS EN1092-2:1997 PN16.
- 4.Test standard:BS EN12266-1 Rate B.

● FEATURES

- Double flange metal seated gate valve
- Size Range:DN50-DN2000
- Standard-ISO/BS/DIN/AWWA/API
- Tests Standard-BS EN 12266-1
- Body Ring-Bronze/SS420/SS304/SS316
- Body-Ductile Iron /Cast Iron/Stainless Steel /WCB
- Fusion bonded epoxy coating-min 300 microns



RELATED PRODUCTS








SMALL DIAMETER GATE VALVE
DN50-DN300,PN10/16/25



METAL SEATED GATE VALVE
DN350-DN600,PN10/16/25



**LARGE DIAMETER
METAL SEATED GATE VALVE**
DN700-DN2000,PN10/16/25

[illegible]

III _____

IV

V 认证: GB, CE, RoHS, Tuv CE, ISO 9001, ADWO-200, TS, PED, WRC WRAS, KTW, API 6D, API609

[illegible]



01

21 years of professional
experience

03

Independent research and
development team
28 top senior professional
researchers

05

100% high level ex-factory
inspection

07

2 years quality assurance,
repair and replacement

4 factories

02

2 professional testing
centers

04

High quality imported
materials

06

COMPANY QUALIFICATION



COMPANY EXHIBITION



Partners



Delivery



Payment



□□□□□□□□□□□□□□

□□□: □□□□□□□□□□□□□□□□□□ □□□□□□□□□□□□□□□□□□□□□□

□□□: □□□□□□□□□□ □□□□□□□□ □□□□□□ □□□□□□□□□□□□□□□□

□□□: □□□□□□□□□□□□□□□□□□□□□□□□ □□□□□□□□□□□?

□□□: □□□□□□□□, □□□□□□, Hrdraulic, □□□□□□□□□□□□ RKSfluid □□□□□□□□□□□□□□□□□□□□□□□□

[illegible]

□□□ : □□□□□□□□□□□□□□□□□□□□?

`RKSfluid`

D: □□□□□□□□□□□□□□□□

[illegible]

□	:	□	□	□	□	□	□	□
---	---	---	---	---	---	---	---	---

000: 1

□□□: □□□□□□□□□□□□□□□□□□□□?

0000: 0000000000000000 100% 0000000000 0000000000 2 00 00000000000000000000000000000000
 00000000

□□□□□□□□□□□□□□□□ Tuv, Api, Wras, CE, ISO

□□□□□□□□□□□□□□ DIN, ASME, BS EN, JIS, API, Awwa

QUESTION:

A: RKSfluid 27 R&D 70