

RKSfluid®



口径	DN32 - DN2400 (NPS1 1/4-NPS96)
公称压力	PN6 - PN10 - PN16 (ANSI 150)
使用温度	-40°C-120°C
密封材料	丁腈橡胶, 三元乙丙橡胶
适用介质	NBR, EPDM, 海水, 工业用水, 蒸汽
连接形式	Wafer, Lug, U-Section, 法兰

APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport



COMPANY INFORMATION



I 公司宗旨： 秉承“以人为本、诚信至上、服务至上”的经营理念，为客户提供最优质的产品和服务。

II 公司优势： 拥有先进的生产设备和专业的技术团队，产品质量稳定可靠，交货周期短，售后服务周到。

III 公司资质： 拥有多项国家专利证书，通过了 ISO 9001 质量管理体系认证，具备完善的售后服务体系。

IV 公司合作： 与多家知名企业建立了长期稳定的合作关系，产品远销国内外市场。

V 公司认证： GB, 国家强制性认证, 国家强制性认证, TUV CE, ISO 9001, ADWO-2000, TS, PED, WRC WRAS, KTW, API 6D, API609

VI 公司服务： 提供售前咨询、技术支持、安装调试、维护保养、配件供应等全方位服务。



01

21 years of professional experience

03

Independent research and development team
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06

COMPANY QUALIFICATION



COMPANY EXHIBITION



