



RKsfluid®

A key Valve in Flow Control



Butterfly Valve



Ball Valve



Gate Valve



Globe Valve



Check Valve



Pipe Fittings

DESIGN FEATURES

HIGHLY CUSTOMIZABLE

- According to **customer requirements**

OPTIMAL SEALING

- AWWA-C219 **absolutely leakproof**
- Internal ebonite rubber lining

CLASSIC & STURDY DESIGN

- Longitudinal adjustment of **+/- 25mm**
- **Super large** Dia & Even pressures up to **100 bar**
- **Cost-effective**, alternative for duplex stainless steel on desalination application

APPLICATION

- Perfect solution for all standard and non-standard applications in challenging famous projects worldwide
- Desalination, water pipes and **various application**

DURABLE

- ANTI-CORROSION
- Thickness: **Epoxy powder** coating of **150-200µm**
- Temperature : Spraying temperature over **200 °C**. Doesn't fade, even wipe with **diethyl ether**

MATERIAL

- Epoxy powder:  , Earth Best!
- WRAS, KTW-W270, ACS approved materials
- Cast iron: nodularity over **95%!**
- Bolts, nuts & washers: Hot Dip Galvanized or Stainless Steel **AISI316-A4**



APPLICATION SCENARIO



Industrial water application



Hydroelectric generation



Sewage treatment



Water treatment



Water supply and drainage



Water transport



Pipe network in house



Irrigation



Our Factory



Company Advantages

01

21 years of professional experience

03

Independent research and development team
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06

A diagram showing a beam of particles (represented by blue squares) moving from left to right. They encounter a step potential barrier. The region to the left of the barrier is labeled 'Region I' and the region to the right is labeled 'Region II'. The barrier is represented by a blue step. The particles are shown in two groups: one group is in Region I, and another group is in Region II, having passed the barrier. The particles in Region II are shown with a different color (orange) to indicate they are reflected or transmitted particles.

[illegible]

A: 00000000 Hydraulic 0000000000000000

--	--	--	--

A: 2 ~ 5 年間の間に、お客様のニーズに合わせて、製品の改良や新製品の開発を行います。

Q: 価格について

A: 1. 製品の仕様や数量によって異なります。

Q: 品質保証について

A: 100% の品質保証を提供いたします。2 年間の保証期間があり、保証期間内には、製品の修理や交換を行います。

製品の品質は、TUV, API, WRAS, CE, ISO 9001 によって認証されています。

また、製品の設計は、DIN, ASME, BS EN, JIS, API, AWWA などの規格に基づいています。

Q: 製品の納期について

A: RKSfluid の製品は、20 年間の経験と R&D の力により、70 以上の国々で、お客様のニーズに合わせて、製品の改良や新製品の開発を行います。