

DESIGN FEATURES

DURABLE




- No-pin connection, 1 pc blow-out proof stem
- DI/CI Nodularity over 95%

ANTI-CORROSION



- Material: Epoxy powder:  , Earth Best!
- Coating Thickness: 200-250µm
- Spraying temp: over 200°C. Doesn't fade, even wipe with diethyl ether

QUALITY STANDARD



- 100% quality test, follow DIN, ASTM, JIS, GB/T, ISO, BS EN, API
- ONLY ONE Manufacturer get CE certification up to DN1800
- 2 years warranty. 15000 times On-off test, 30000 times Destructive experiment




口径	DN32 - DN2400 (NPS1 1/4-NPS96)
公称压力	PN6 - PN10 - PN16 (Class 150)
使用温度	-40°C-120°C
材料	球墨铸铁, 铸钢, 不锈钢
密封材料	NBR, EPDM, 聚四氟乙烯, 聚氨酯, 橡胶



WAFER



LUG



NPS14-NPS40 Wafer/Lug with alignment holes

Size	L	H1	H2	h	A	ΦB	C	ΦG	a	b	ΦD	n-Φd	ISO5211
NPS14	3.07	10.63	11.81	1.42	1.06	Φ13.31	12.95	-	-	-	Φ4.92	4-Φ0.55	F12
NPS16	4.02	11.81	13.58	1.69	1.26	Φ15.35	14.80	-	-	-	Φ5.50	4-Φ0.71	F14
NPS18	4.49	12.99	14.76	1.93	4.42	Φ17.20	16.61	-	-	-	Φ5.50	4-Φ0.71	F14
NPS20	5.00	15.16	16.73	2.56	-	Φ19.09	18.43	Φ2.36	0.71	2.52	Φ6.50	4-Φ0.87	F16
NPS24	6.06	17.24	19.49	2.76	-	Φ23.03	22.24	Φ2.36	0.71	2.52	Φ6.50	4-Φ0.87	F16
NPS28	6.50	20.39	22.44	3.15	-	Φ26.77	25.98	Φ2.76	0.79	2.93	Φ10.00	8-Φ0.71	F25
NPS30	6.50	21.46	24.02	3.15	-	Φ28.74	27.95	Φ2.76	0.79	2.93	Φ10.00	8-Φ0.71	F25
NPS32	7.48	22.32	25.20	3.15	-	Φ30.43	29.49	Φ2.76	0.79	2.93	Φ10.00	8-Φ0.71	F25
NPS36	7.99	25.59	27.56	3.94	-	Φ34.49	33.54	Φ3.15	0.87	3.35	Φ10.00	8-Φ0.71	F25
NPS40	8.50	28.15	29.53	3.94	-	Φ38.43	37.48	Φ3.15	0.87	3.35	Φ11.73	8-Φ0.87	F30

APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport



COMPANY INFORMATION



I 企业简介: 公司位于中国山东省潍坊市, 是一家专业从事水处理设备研发、生产、销售和服务的高新技术企业。

II 公司主要产品: 包括各种规格的水处理过滤器、反渗透膜组件、超滤膜组件、微滤膜组件、以及配套的水处理控制系统。

III 公司主要客户: 主要为国内外的工业企业和市政供水部门, 产品广泛应用于食品饮料、医药化工、电子工业、市政供水等领域。

IV 公司主要荣誉: 公司拥有多项国家专利, 并通过了 ISO 9001 质量管理体系认证和 ISO 14001 环境管理体系认证。

V 公司主要标准: GB, 行业标准, 企业标准, TUV CE, ISO 9001, ADWO-2000, TS, PED, WRC WRAS, KTW, API 6D, API609

VI 公司主要合作伙伴: 与国内外知名企业和科研机构建立了长期合作关系, 共同研发和推广先进的水处理技术。



01

21 years of professional experience

03

Independent research and development team
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06


COMPANY QUALIFICATION



COMPANY EXHIBITION



Partners



0000: 0000000000000000 0000000000000000
 0000: 000000000000 00000000 00000000 00000000 000000000000

問問: 請問各位工程師對於目前市面上所販售的 各種減壓閥有研究嗎?
 問問: 請問目前, 市面上, Hrdraulic, 各種減壓閥與 RKSfluid 減壓閥有何不同之處?
 問問: 請問各位工程師對於目前市面上所販售的 各種減壓閥有研究嗎?

□□□ : □□□□□□□□□□□□□□□□□□□□□□?

Q: RKSfluid 製品はどのような用途に使用されますか？

A: 主に工業用流体の制御に使用されます。

Q: 製品のサイズはどのくらいありますか？

A: 標準サイズは 2 ~ 5 mm です。

Q: 1 台あたりの価格はいくらですか？

A: 製品は現在市場に出回っておりません。

A: 製品の品質は 100% 保証されています。2 年間の保証期間があります。

製品の品質は 100% 保証されています。2 年間の保証期間があります。

製品の品質は 100% 保証されています。2 年間の保証期間があります。

製品の品質は 100% 保証されています。2 年間の保証期間があります。

Q: 製品の仕様はどのようなものがありますか？

A: RKSfluid 製品は、現在市場に出回っておりません。20 年間の保証期間があります。R&D 部門は 70 名で構成されています。

製品の品質は 100% 保証されています。2 年間の保証期間があります。