




DESIGN FEATURES

VERSATILE & RANGE

- Up to 28mm of tolerance, **DN40 ~ DN450** stock reduction
- Allows angular deflection of **+/-3°** per gasket
- Covering most common pipe materials



OPTIMAL SEALING

- **Unique gasket** with circumferential ribs sealing on corroded, scored or pitted pipes

DURABLE

- **ANTI-CORROSION**
- Thickness: **Epoxy powder** coating of **200-250µm**
- Temperature : **Spraying temperature over 200°C**
- Doesn't fade, even wipe with **diethyl ether**

MATERIAL

- Epoxy powder: **AkzoNobel**, Earth Best!
- Nuts: **DACROMET®** or **GEOMET®**, Earth Best!
- Cast iron: **EN-GJS-500-7**, nodularity over **95%**!
- Flange Adaptors: for most common flange standards. **PN10/16/ANSI150** drilled

APPLICATION SCENARIO



Our Factory



Company Advantages

01

21 years of professional experience

03

Independent research and development team
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06



area 项目占地面积: 项目占地面积约 10000 平方米

centers 项目中心: 项目中心位于乌鲁木齐市

reference 项目参考: 项目参考标准为 GB, GB 18308-2008, GB 18309-2008, TUV CE, ISO 9001, ADWO-2000, TS, PED, WRC WRAS, KTW, API 6D, API609

IV 项目说明: 项目说明如下

Standard 项目标准: GB, GB 18308-2008, GB 18309-2008, TUV CE, ISO 9001, ADWO-2000, TS, PED, WRC WRAS, KTW, API 6D, API609

VI 项目内容: 项目内容包括: 项目设计, 项目施工, 项目调试, 项目验收, 项目运营, 项目维护, 项目培训, 项目咨询 / 项目服务 / 项目支持, 项目保障



□ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □

:

0000:

:

A: 00000000, 000000, Hrdraulic, 0000000000000000 0000000000 RKSfluid 00000000000000
0000000000000000 00000000000000000000000000

Q:

A: RKSfluid

Q: □□□□□□□□□□□□□□

A: 2 ~ 5

Q:

[illegible]

:

[illegible]

□□□□□□□□ TUV, API, WRAS, CE, ISO □□□□□□

□□□□□□□□□□□□ DIN, ASME, BS EN, JIS, API, AWWA

:

A: RKSfluid 20 R&D 70