



RKSfluid®

A key Valve in Flow Control



Butterfly Valve



Ball Valve



Gate Valve



Globe Valve




Check Valve



Pipe Fittings

DESIGN FEATURES

- RANGE**
- For CI, DI, STL and AC pipes
 - **DN50-DN1000**
 - The body & gasket fit **9 kinds of pipe** with nominal diameters
 - The saddles – Can be used for **all pipe types**



- RELIABLE**
- **EPDM gasket** to EN681-1, mechanically inserted on Series 1425

- ANTI-CORROSION**
- Epoxy or cathodolysis coating
 - Thickness: Epoxy powder coating of **200-250µm**
 - Temperature : Spraying temperature over **200 °C**. Doesn't fade, even wipe with **diethyl ether**.

MATERIAL

- Epoxy powder:  , Earth Best!
- Nuts: **DACROMET®** or **GEOMET®** , Earth Best!
- Cast iron: **EN-GJS-400-15**, nodularity over **95%**!



APPLICATION SCENARIO



Industrial water application



Hydroelectric generation



Sewage treatment



Water treatment



Water supply and drainage



Water transport



Pipe network in house



Irrigation



Our Factory



Q: 100% 100% 100% 100% 100% 100% 100% 100% 100% 100%

A: RKSfluid 100% 100% 100% 100% 100% 100% 100% 100% 100% 100%

Q: 100% 100% 100% 100% 100% 100% 100% 100% 100% 100%

A: 100% 100% 100% 100% 100% 100% 100% 100% 100% 100%

Q: 100% 100% 100% 100% 100% 100% 100% 100% 100% 100%

A: 1 100% 100% 100% 100% 100% 100% 100% 100% 100% 100%

100%: 100% 100% 100% 100% 100% 100% 100% 100% 100% 100%

A: 100% 100% 100% 100% 100% 100% 100% 100% 100% 100%

TUV, API, WRAS, CE, ISO 100%

DIN, ASME, BS EN, JIS, API, AWWA

100%: 100% 100% 100% 100% 100% 100% 100% 100% 100% 100%

A: RKSfluid 100% 100% 100% 100% 100% 100% 100% 100% 100% 100%