



## DESIGN FEATURES

### DURABLE

- No-pin connection, 1 pc blow-out proof stem
- DI/CI Nodularity over 95%

### ANTI-CORROSION

- Material: Epoxy powder:  , Earth Best!
- Coating Thickness: 200-250µm
- Spraying temp: over 200°C. Doesn't fade, even wipe with diethyl ether

### QUALITY STANDARD

- 100% quality test, follow DIN, ASTM, JIS, GB/T, ISO, BS EN, API
- ONLY ONE Manufacturer get CE certification up to DN1800
- 2 years warranty. 15000 times On-off test, 30000 times Destructive experiment





## APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport



# Our Factory



## Company Advantages

01

21 years of professional experience

03

Independent research and development team  
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06



I 工厂名称: 江苏瑞斯流体设备有限公司

centers 工厂地址: 江苏省无锡市新吴区新锦路100号

reference 工厂电话: 0510-88588888

IV 工厂网址: [www.rksfluid.com](http://www.rksfluid.com)

Standard 工厂标准: GB, 行业标准, 国际标准, TUV CE, ISO 9001, ADWO-2000, TS, PED, WRC WRAS, KTW, API 6D, API609

VI 工厂认证: [ISO 9001](#), [ISO 14001](#), [OHSAS 18001](#), [API 6D](#), [API 609](#), [PED](#), [WRC WRAS](#), [KTW](#), [TUV CE](#)



