

DESIGN FEATURES

DURABLE




- No-pin connection, 1 pc blow-out proof stem
- DI/CI Nodularity over 95%

ANTI-CORROSION

- Material: Epoxy powder:  , Earth Best!
- Coating Thickness: 200-250µm
- Spraying temp: over 200°C. Doesn't fade, even wipe with diethyl ether

QUALITY STANDARD



- 100% quality test, follow DIN, ASTM, JIS, GB/T, ISO, BS EN, API
- ONLY ONE Manufacturer get CE certification up to DN1800
- 2 years warranty. 15000 times On-off test, 30000 times Destructive experiment





□□□□	DN32 - DN2400 □NPS1 1/4 -NPS96)
□□□□□□□□□□	PN6 - PN10 - PN16 (□□□□ 150)
□□□□□□□□□□	-40 °C-120 °C
□□□□□	□□□□□□□□□□□□□□ □□□
□□□□□□□□□□	NBR, EPDM, □□□□□□□□□□, □□□□□□□, Viton

□□□□□□□□□□


□□□□□□, lug, u-section, double flange



WAFER



LUG



NPS14-NPS40 Wafer/Lug with alignment holes

Size	L	H1	H2	h	A	ΦB	C	ΦG	a	b	ΦD	n-Φd	ISO5211
NPS14	3.07	10.63	11.81	1.42	1.06	Φ13.31	12.95	-	-	-	Φ4.92	4-Φ0.55	F12
NPS16	4.02	11.81	13.58	1.69	1.26	Φ15.35	14.80	-	-	-	Φ5.50	4-Φ0.71	F14
NPS18	4.49	12.99	14.76	1.93	4.42	Φ17.20	16.61	-	-	-	Φ5.50	4-Φ0.71	F14
NPS20	5.00	15.16	16.73	2.56	-	Φ19.09	18.43	Φ2.36	0.71	2.52	Φ6.50	4-Φ0.87	F16
NPS24	6.06	17.24	19.49	2.76	-	Φ23.03	22.24	Φ2.36	0.71	2.52	Φ6.50	4-Φ0.87	F16
NPS28	6.50	20.39	22.44	3.15	-	Φ26.77	25.98	Φ2.76	0.79	2.93	Φ10.00	8-Φ0.71	F25
NPS30	6.50	21.46	24.02	3.15	-	Φ28.74	27.95	Φ2.76	0.79	2.93	Φ10.00	8-Φ0.71	F25
NPS32	7.48	22.32	25.20	3.15	-	Φ30.43	29.49	Φ2.76	0.79	2.93	Φ10.00	8-Φ0.71	F25
NPS36	7.99	25.59	27.56	3.94	-	Φ34.49	33.54	Φ3.15	0.87	3.35	Φ10.00	8-Φ0.71	F25
NPS40	8.50	28.15	29.53	3.94	-	Φ38.43	37.48	Φ3.15	0.87	3.35	Φ11.73	8-Φ0.87	F30

APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport



COMPANY INFORMATION



i) 本公司擁有先進的生產設備和技術，能夠生產各種規格、品種的鋼管，並可根據客戶的要求進行定製。

ii) 本公司擁有先進的 CNC 加工設備，能夠生產各種規格、品種的鋼管，並可根據客戶的要求進行定製。

iii) 本公司擁有先進的生產設備和技術，能夠生產各種規格、品種的鋼管，並可根據客戶的要求進行定製。

iv) 本公司擁有先進的生產設備和技術，能夠生產各種規格、品種的鋼管，並可根據客戶的要求進行定製。

v) 本公司擁有先進的生產設備和技術，能夠生產各種規格、品種的鋼管，並可根據客戶的要求進行定製。

VI) 本公司擁有先進的生產設備和技術，能夠生產各種規格、品種的鋼管，並可根據客戶的要求進行定製。



01

21 years of professional experience

03

Independent research and development team
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06


COMPANY QUALIFICATION



COMPANY EXHIBITION



Partners



問: 如何處理這批被檢出的偽鈔？
答: 已通知有關當局，由他們處理。

A: `hrdr`, `hrdfluid`, `hrdrfluid`

QUESTION: What are the main components of a business plan?

A: RKSfluid 100% 100% 100% 100% 100% 100% 100% 100% 100% 100%

Q: 100% 100%

Q: 100% 100% 100% 100% 100% 100% 100% 100% 100% 100%

Q: **MOQ**

A: 1pc 100% 100% 100% 100%

Q: 100% 100% 100% 100% 100% 100% 100% 100% 100% 100%?

Q: 100% 100% 100% 100% 100% 100% 100% 100% 100% 100%

100% 100% 100% 100% 100% 100% 100% 100% 100% 100%

100% 100% 100% 100% 100% 100% 100% 100% 100% 100%

100% 100% 100% 100% 100% 100% 100% 100% 100% 100%

Q: 100% 100% 100% 100% 100% 100% 100% 100% 100% 100%?

A: RKSfluid 100% 100% 100% 100% 100% 100% 100% 100% 100% 100%

100% 100% 100% 100% 100% 100% 100% 100% 100% 100%