

## DESIGN FEATURES

This series of butterfly valves are used for industrial pipelines, as bi-directional open and close and regulation devices, the adjustment range is from 40°C-90°C full open. Suitable temperature  $\geq 80^{\circ}\text{C}$

### Features

- Size range DN100-1200mm
- Standard-ISO/BS/DIN/AWWA/API
- Tests Standard-BS EN 12266-1
- Body-Ductile Iron/Cast Iron/Stainless Steel /WCB
- Body Ring-SS420/SS304/SS316
- Disc Ring-EPDM
- Shaft-SS420/SS431/SS316
- Fusion bonded epoxy coating-Min 300 Microns



# APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport





# COMPANY FACTORY



# COMPANY INFORMATION



i) 本公司拥有先进的生产设备，包括数控机床、加工中心、磨床、铣床、刨床、钻床、冲床、折弯机、剪板机、卷板机等，能够满足各种规格和材质的加工需求。

ii) 本公司拥有完善的质量管理体系，通过了 ISO 9001 质量管理体系认证，并配备了专业的检测设备和人员，能够为客户提供准确的质量检测报告。

unit 本公司拥有专业的技术团队，具备丰富的行业经验，能够为客户提供专业的技术咨询和方案设计，确保产品质量和交货周期。

iv) 本公司拥有完善的生产流程，从原材料采购到成品出厂，每一个环节都严格把控，确保产品质量和交货周期。

v) 本公司拥有完善的质量管理体系，通过了 GB, ADWO-2000, TS, PED, WRC WRAS, KTW, API 6D, API609 等认证，能够满足客户的各种需求。

VI) 本公司拥有完善的质量管理体系，通过了 GB, ADWO-2000, TS, PED, WRC WRAS, KTW, API 6D, API609 等认证，能够满足客户的各种需求。





## COMPANY QUALIFICATION





