



RKsfluid®

A key Valve in Flow Control



Butterfly Valve



Ball Valve



Gate Valve



Globe Valve



Check Valve



Pipe Fittings

Product Description



Super Anti-corrosion
Epoxy powder coating **200-250µm**,
baking varnish over **200°C**,
use  material.



Free wedge nut, **reduces the stem bending forces** and at the same time enables it to be easily replaced.



The more compact new cap, reduces the water retention areas in order to **reduce the risk of bacterial growth**.



One piece stainless steel stem in for **better resistance to axial load and to with stand higher operating torques**.



Three locking tab for bayonet system prevents self-dismantling.



Dust guard integrating three O-ring shape, **prohibiting the introduction of foreign** bodies at the stem.



Male guiding system with composite sliding skate reduces the wear of the wedge against the body, allowing a smooth functionality and a longer life time of the valve.



Triple seal at the operating stem to ensure tightness with the test of time (2500 cycles).



New male composite sliding skate technology ensuring a low operating torque even under high differential pressure and preventing damage or corrosion generated by the friction.

Engineering Projects



Product Category



PTFE lined butterfly valve



Resilient seat butterfly valve



Double offset butterfly valve



Triple offset butterfly valve



Ball valve



Pipe fittings

Four factories



Why choose us



- 2 professional testing centers
- 28 senior professional researchers
- Independent research and development team



- 21 years of professional experience
- 100% high level ex-factory inspection
- 2 years quality assurance, repair and replacement

Exhibition Photos



Our Certificates



□ □ □ □ □ □ □ □ □ □ □ □ □ □

[illegible]

A: 0000000000, 00000000, 0000000, 000000000, 0000000000000000

[illegible]

A: 鋼製、鋁製、銅製、樹脂製の各種ポンプに RKSfluid を適用することが可能です。
ポンプの種類や材質によって適用の仕方が異なります。

Q: どのようなポンプに適用できますか？

A: 鋼製ポンプに RKSfluid を適用することが可能です。

Q: 適用の仕方は？

A: ポンプの種類によって適用の仕方が異なります。2 - 5 分で完了します。

Q: 適用の回数？

A: ポンプの種類によって適用の回数が異なります。1 回です。

Q: 適用のメリット？

A: ポンプの種類によって適用の仕方が異なります。100% の適用が可能です。2 分で完了します。

適用の仕方は TUV, API, WRAS, CE, ISO があります。

適用の仕方は DIN, ASME, BS EN, JIS, API, AWWA があります。

Q: 適用のデメリット？

A: RKSfluid を適用すると 20 分で完了します。70 分で完了します。