RKSfluid®
A key Valve in Flow Control
Butterfly Valve
Ball Valve
Gate Valve
Globe Valve
Check Valve
Pipe Fittings

DESIGN FEATURES

VERSATILE & RANGE

- Up to 27mm of tolerance, DN40 ~ DN300 stock reduction
- Allows angular deflection of +/-5°
- Covering most common pipe materials

DI — Ductile Iron
CI — Cast Iron
PVC — Poly Vinyl Chloride
STL — Steel
GRP — Glass fibre reinforced plastic
AC — Fibre Cement

USER FRIENDLY

- Economical and applicable
- Easy Operation

OPTIMAL SEALING

- Unique gasket with circumferential ribs sealing on corroded, scored or pitted pipes

DURABLE

- Anti-corrotion
- Thickness: Epoxy powder coating of 200-250μm
- Temperature : Spraying temperature over 200 ℃. Doesn't fade, even wipe with diethyl ether

MATERIAL

- Epoxy powder: AkzoNobel, Earth Best!
- Nuts: DACROMET® or GEOMET®, Earth Best!
- Cast iron: EN-GJS-500-7, nodularity over 95%!

APPLICATION SCENARIO

Industrial water application | Hydroelectric generation | Sewagetreatment | Water treatment | Water supply and drainage | Water transport | Pipe network in house | Irrigation

Our Factory

Company Advantages
01
21 years of professional experience
02
4 factories
03
Independent research and development team
28 top senior professional researchers
04
2 professional testing centers
05
100% high level ex-factory inspection
06
High quality imported materials
07
2 years quality assurance, repair and replacement

RKSfluid
RKSfluid

I[illegible]: [illegible]

II[illegible]

III[illegible]

IV[illegible]

V□□□□□□□□□□□□□□□□□□□: GB, German Standard, American Standard, TUV CE, ISO 9001, ADWO-2000, TS, PED, WRC WRAS, KTW, API 6D, API609

VI □□□□□□□□□□□□: □□□□□□□□□□□□□, □□□□□□□□□□, □□□□□□□□□□□□, □□□□□□□□□□□□□□, □□□□□□□□□□, □□□□□□□□□□□, □□□□□□□□□□□□□□□□□□□□□□□□□□□ / □□□□□□□□□□ / □□□□□□, □□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□□□□□

□□□: □□□
□□□: □□

□□□: □□□?
□□□: □□□□□□□□□□, □□□□□□, □□□□□□□□□□, □□□□□□□□□□□□□□□□□□ □□□□□□□□□□□□□□□ RKSfluid □□□□□□□□□□□□□□□□□□□□ □□□□□□□□□□□□□□ □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

□□□: □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□?
□□□: RKSfluid □□

□□□: □□□□□□□□□□□□□□□□
□□□: □□□□□□□□□□□□□□□□□□□□□ 2 ~ 5 □□□□□□□□ □□□□□□□□□□□□□□□□□□□□□□□□□□□

□□□: □□□□□□□□
A: 1pc □□□□□□□□□□□□□□□□□□□□□□

□□□: □□□□□□□□□□□□□□□□□□□□□□□□□?
A: □□□□□□□□□□ 100% □□□□□□□□□□□□□□□□□□ 2 □□ □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□
□□
□□□□□□□□□□□□□□□□□ TUV, API, WRAS, CE, ISO
□□□□□□□□□□□□□□□ DIN, ASME, BS EN, JIS, API, AWWA

□□□: □□?
□□□: RKSfluid □□□□□□□□□□□□ 20 □□□□□□□□□□ R&D □□□□□□□ 70 □□□□□□□□□□□□□□□□□□□□□□□□□
□□□