RKSfluid®
A key Valve in Flow Control
Butterfly Valve
Ball Valve
Gate Valve
Globe Valve
Check Valve
Pipe Fittings

Product Description

Super Anti-corrosion

Epoxy powder coating 200-250μm,

baking varnish over 200℃,

use AkzoNobel material.

Free wedge nut, reduces the stem bending forces and at the same time enables it to be easily replaced.

The more compact new cap, reduces the water retention areas in order to reduce the risk of bacterial growth.

One piece stainless steel stem in for better resistance to axial load and to with stand higher operating torques.

Three locking tab for bayonet system prevents self-dismantling.

Dust guard integrating three O-ring shape, prohibiting the introduction of foreign bodies at the stem.

Male guiding system with composite sliding skate reduces the wear of the wedge against the body, allowing a smooth functionality and a longer life time of the valve.

Triple seal at the operating stem to ensure tightness with the test of time (2500 cycles).

New male composite sliding skate technology ensuring a low operating torque even under high differential pressure and preventing damage or corrosion generated by the friction.

Engineering Projects

Product Category

PTFE lined butterfly valve

Resilient seat butterfly valve

Double offset butterfly valve

Triple offset butterfly valve

Ball valve

Pipe fittings

[illegible]I[illegible]: [illegible]

[illegible]II[illegible]

[illegible]III[illegible]

IV[illegible], [illegible]

V[illegible]: GB [illegible], TUV CE, ISO 9001, ADWO-2000, TS, PED, WRC WRAS, KTW, API 6D, API609

[illegible] VI [illegible]: [illegible], [illegible], [illegible], [illegible], [illegible], [illegible] / [illegible] / [illegible], [illegible]

Why choose us

- 2 professional testing centers
- 28 senior professional researchers
- Independent research and development team



- 21 years of professional experience
- 100% high level ex-factory inspection
- 2 years quality assurance, repair and replacement

Exhibition Photos

Our Certificates

□□□□□□□□□□□□□□□□□□

Q: □□?
A: □□□□□□□□□□□□, □□□□□□□□□□, □□□□□□□□, □□□□□, □□□□ Appllication

Q: □□□?

A: [illegible], [illegible], Hrdraulic, [illegible] [illegible] RKSfluid [illegible]

Q: [illegible]
A: RKSfluid [illegible]

Q: [illegible]
A: [illegible] 2 ~ 5 [illegible] [illegible]

Q: [illegible]
A: 1pc [illegible]

Q: [illegible]
A: [illegible] 100% [illegible] 2 [illegible] [illegible]
[illegible] TUV, API, WRAS, CE, [illegible] ISO
[illegible] DIN, ASME, BS EN, JIS, API, AWWA

Q: [illegible]
A: RKSfluid [illegible] 20 [illegible] R & D [illegible] 70 [illegible]