



RKSfluid®

A key Valve in Flow Control



Butterfly Valve



Ball Valve



Gate Valve



Globe Valve



Check Valve



Pipe Fittings

Product Description



Super Anti-corrosion
Epoxy powder coating **200-250µm**,
baking varnish over **200°C**,
use  material.



Free wedge nut, **reduces the stem bending forces** and at the same time enables it to be easily replaced.



The more compact new cap, reduces the water retention areas in order to **reduce the risk of bacterial growth**.



One piece stainless steel stem in for **better resistance to axial load and to with stand higher operating torques**.



Three locking tab for bayonet system prevents self-dismantling.



Dust guard integrating three O-ring shape, **prohibiting the introduction of foreign bodies** at the stem.



Male guiding system with composite sliding skate reduces the wear of the wedge against the body, allowing a smooth functionality and a longer life time of the valve.



Triple seal at the operating stem to ensure tightness with the test of time (2500 cycles).



New male composite sliding skate technology ensuring a low operating torque even under high differential pressure and preventing damage or corrosion generated by the friction.

Our Factory



i) 工厂拥有完善的质量管理体系，通过了 ISO 9001 认证，确保了产品的质量和稳定性。

ii) 工厂拥有先进的生产设备和技术，能够满足客户对高精度、高质量产品的需求。

unction 工厂拥有专业的研发团队，能够为客户提供定制化的产品和服务。

iv) 工厂拥有完善的销售网络，能够为客户提供及时、专业的售后服务。

v) 工厂拥有完善的质量管理体系，通过了 GB, CE TUV, ISO 9001, 等认证。

Four factories



Why choose us



- 2 professional testing centers
- 28 senior professional researchers
- Independent research and development team



- 21 years of professional experience
- 100% high level ex-factory inspection
- 2 years quality assurance, repair and replacement

Q: RKSfluid, Hydraulic, RKSfluid Actuators
A: RKSfluid

Q: RKSfluid
A: RKSfluid

D: RKSfluid
A: RKSfluid 2 ~ 5

D: RKSfluid
A: 1 RKSfluid

Q: RKSfluid
A: RKSfluid 100% RKSfluid 2
RKSfluid TUV, API, WRAS, CE, RKSfluid ISO
RKSfluid DIN, ASME, BS EN, JIS, API, AWWA

Q: RKSfluid
A: RKSfluid 20 RKSfluid 70 RKSfluid