



## DESIGN FEATURES

### DURABLE

- No-pin connection, 1 pc blow-out proof stem
- DI/CI Nodularity over 95%

### ANTI-CORROSION

- Material: Epoxy powder:  , Earth Best!
- Coating Thickness: 200-250µm
- Spraying temp: over 200°C. Doesn't fade, even wipe with diethyl ether

### QUALITY STANDARD

- 100% quality test, follow DIN, ASTM, JIS, GB/T, ISO, BS EN, API
- ONLY ONE Manufacturer get CE certification up to DN1800
- 2 years warranty. 15000 times On-off test, 30000 times Destructive experiment







## APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport







## Company Advantages

01

21 years of professional experience

03

Independent research and development team  
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06







Q: 100% hydraulic fluid? (100% hydraulic fluid?)

A: Yes, hydraulic, Hrdraulic, 100% hydraulic fluid RKSfluid 100% hydraulic fluid

Q: 100% hydraulic fluid? (100% hydraulic fluid?)

A: RKSfluid 100% hydraulic fluid

Q: 100% hydraulic fluid? (100% hydraulic fluid?)

A: 100% hydraulic fluid 2 ~ 5 years

Q: 100% hydraulic fluid? (100% hydraulic fluid?)

A: 1pc 100% hydraulic fluid

Q: 100% hydraulic fluid? (100% hydraulic fluid?)

A: 100% hydraulic fluid 100% hydraulic fluid 2 years TUV, API, WRAS, CE, ISO DIN, ASME, BS EN, JIS, API, AWWA

Q: 100% hydraulic fluid? (100% hydraulic fluid?)

A: RKSfluid 20 years R & D 70 years