

Product Description



Super Anti-corrosion
Epoxy powder coating **200-250µm**,
baking varnish over **200°C**,
use  material.



Free wedge nut, **reduces the stem bending forces** and at the same time enables it to be easily replaced.



The more compact new cap, reduces the water retention areas in order to **reduce the risk of bacterial growth**.



One piece stainless steel stem in for **better resistance to axial load and to with stand higher operating torques**.



Three locking tab for bayonet system prevents self-dismantling.



Dust guard integrating three O-ring shape, **prohibiting the introduction of foreign bodies** at the stem.



Male guiding system with composite sliding skate reduces the wear of the wedge against the body, allowing a smooth functionality and a longer life time of the valve.



Triple seal at the operating stem to ensure tightness with the test of time (2500 cycles).



New male composite sliding skate technology ensuring a low operating torque even under high differential pressure and preventing damage or corrosion generated by the friction.

Design standard

Design standard	BS EN 1171 ANSI
Flange	GB/T 17241.6-2008、 DIN 2633-1975、 BS EN1902-2
Face to face	GB/T 12221-2005、 ISO 5752-1988、 BS EN558-1(F4、 F5)
Test standard	EN12266

Specification

Size	DN50-900
Pressure	PN10 PN16 class150
Medium	Water
Temperature	0°C~90°C

PRODUCT DISPLAY



SHIPPING PACKAGING



COMPANY INFORMATION



i. 我们的工厂配备了： 先进的自动化生产设备， 专业的技术人员， 完善的质量管理体系， 以及先进的物流系统。

ii. 我们拥有先进的 CNC 加工中心， 专业的研发团队， 完善的售后服务体系， 以及先进的物流系统。

COMPANY FACTORY



EXHIBITION



Q: 貴社の製品はどのような規格に準拠していますか？

A: 100% 検査を実施し、2 年

保証を提供いたします。

認証取得済み TUV, API, WRAS, CE, ISO

規格に準拠しています。DIN, ASME, BS EN, JIS, API, AWWA

Q: 貴社の製品はどのような用途に使用されていますか？

A: RKSfluid は 20 年間の R&D を経て、70

以上の国産メーカーと同等の品質を実現しています。