



# RKSfluid®

A key Valve in Flow Control



Butterfly Valve

Ball Valve

Gate Valve

Globe Valve

Check Valve

Pipe Fittings

## DESIGN FEATURES

### TECHNICAL REQUIREMENT :

- 1.Design standard: BS 5163.
- 2.Face to face: BS 5163.
- 3.Flanges standard: BS EN1092-2: 1997 PN16.
- 4.Test standard: BS EN12266-1 Rate B.

### FEATURES :

- ◆ Double flange metal seated gate valve
- ◆ Size Range: DN50-DN2000
- ◆ Standard -ISO / BS /DIN / AWWA /API
- ◆ Tests Standard-BS EN 12266-1
- ◆ Body Ring-Bronze /SS420 /SS304 /SS316
- ◆ Disc Ring-Bronze /SS420 /SS304 /SS316
- ◆ Stem-Stainless Steel SS420 /SS431 /SS316
- ◆ Body-Ductile Iron / Cast Iron/Stainless Steel /WCB
- ◆ Disc-Ductile Iron /Cast Iron/Stainless Steel /WCB
- ◆ Fusion bonded epoxy coating-min 300 microns



RKS SMALL DIAMETER GATE VALVE  
DN50 - DN300, PN10 / 16 /25

RKS METAL SEATED GATE VALVE  
DN350 - DN600, PN10 / 16 /25

RKS LARGE DIAMETER METAL SEATED GATE VALVE  
DN700 - DN2000, PN10 / 16 /25

### APPLICATION SCENARIO



# Our Factory



Fluid RKS 1997 GB



## Exhibition Photos

