

PRODUCT STRUCTURE

Features

- Size range DN100-1200mm
- Standard-ISO/ BS/DIN /AWWA/API
- Tests standard-BS EN 12266-1
- Body-Ductile Iron/Cast Iron/Stainless Steel/WCB
- Body Ring-SS420/SS304/SS316
- Disc Ring-EPDM
- Shaft-420/S5431/SS316
- Fusion bonded epoxy coating- Min 300 Microns

This series tilting check valves are suitable to be used at the exit of the pump whose medium is water. It is used to prevent or reduce medium back from water hammer. So it can protect the pipeline system. Suitable temperature $\leq 80^{\circ}\text{C}$



APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport



COMPANY FACTORY



COMPANY INFORMATION



i) 公司所有产品均符合：GB 19001-2016/ISO 9001:2015 质量管理体系标准

ii) 公司所有产品均符合：GB 19001-2016/ISO 9001:2015 质量管理体系标准，GB 19001-2016/ISO 9001:2015 质量管理体系标准，GB 19001-2016/ISO 9001:2015 质量管理体系标准

unction 公司所有产品均符合：GB 19001-2016/ISO 9001:2015 质量管理体系标准，GB 19001-2016/ISO 9001:2015 质量管理体系标准

iv) 公司所有产品均符合：GB 19001-2016/ISO 9001:2015 质量管理体系标准

v) 公司所有产品均符合：GB, 质量管理体系标准, TUV CE, ISO 9001, ADWO-2000, TS, PED, WRC WRAS, KTW, API 6D, API609

VI) 公司所有产品均符合：质量管理体系标准, 质量管理体系标准, 质量管理体系标准, 质量管理体系标准, 质量管理体系标准, 质量管理体系标准 / 质量管理体系标准 / 质量管理体系标准, 质量管理体系标准

01

21 years of professional experience

03

Independent research and development team
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06

COMPANY QUALIFICATION



COMPANY EXHIBITION



